



CLAVE	CAP. (TON)	LARGO DE CADENA (METROS)	PESO (KG)	ESLABÓN MM (CADENA)		FUERZA (N)	MILÍMETROS						REFACCIONES							
				X	Y		A	B	C	D	E	H (ALTURA MIN.)	CADENA	BALATAS	TRINQUETE	GATILLO	RESORTE	PESTILLO	ENSAMBLE DE GANCHO	
HB5010	0.75	1.5	6.9	6	18	265	148	87	132	35.5	278	27	330	HB5050	HB5105	HB5113	HB5118	HB5148	HB5145	HB5156
HB5011	1	1.5	7.9	6	18	270	153	90	140	37.5	278	29	365	HB5050	HB5105	HB5113	HB5118	HB5148	HB5141	HB5157
HB5012	1.5	1.5	10.9	7	21	295	173	99	145	42.5	378	33.5	400	HB5055	HB5106	HB5114	HB5119	HB5148	HB5146	HB5158
HB5013	3	1.5	20.7	10	30	335	200	112	199	50	418	40	520	HB5065	HB5107	HB5115	HB5119	HB5149	HB5143	HB5160
HB5014	6	1.5	28.1	10	30	370	200	112	230	53	418	42.5	640	HB5065	HB5107	HB5115	HB5119	HB5149	HB5147	HB5162



CLAVES CADENAS	TIPO	LARGO DE CADENA (METROS)	ESLABÓN MM (CADENA)	
			X	Y
HB5050	Grado 80	10	6	18
HB5055	Grado 80	6	7	21
HB5065	Grado 80	10	10	30



- Facilitan el mantenimiento
- Cumplen con las normas internacionales de seguridad más estrictas como CE, TUV y GS