

Impact Accessory

8260

- Extension bar
- DIN 3121



8260P

1"

8869

- Adapter
- Convert to 1-1/2" drive
- DIN 3121



8869P


1"

KT NO.	Overall Length		g	g
	Inch	mm		
8260-07	7	175	1400	1 / 12
8260-10	10	250	1932	1 / 12
8260-13	13	330	2458	1 / 8
8260-07P	7	175	1400	1 / 12
8260-10P	10	250	1932	1 / 12
8260-13P	13	330	2458	1 / 8

KT NO.	Spec.	g	g
8869	1" F x 1-1/2"M	941	1 / 24
8869P	1" F x 1-1/2"M	941	1 / 24

8797

- Universal joint
- DIN 3121



8797P

1"



KT NO.	Overall Length		D mm	g	g
	Inch	mm			
8797	5	125	60	1491	1 / 18
8797P	5	125	60	1491	1 / 18

90405

- Locking ring
- High tensile rubber material

90406


1"

90605

- Locking pin
- Chrome vanadium steel
- DIN 3129

90606

1"



90605
90606

90405
90406

KT NO. Type \varnothing d / l Applied to socket sizes

90405	ring	5.5	44	8535M (19~70mm) 8435M (24~60mm) 8835M (24~60mm)	8535S (3/4"-2-3/4") 8435S (15/16"-2-1/4")
90605	pin	5.0	45	8514M.8514S.8534M.806519M 8260.8797.8866.8869	
90406	ring	10	75	8535M (71~90mm)	8535S (2-13/16"-3-1/2")
90606	pin	5.0	75		

8866

- Adapter
- Convert to 3/4" drive
- 8866 → Max. torque : 1412 N·m
- DIN 3121



8866P

1"

KT NO.	Spec.	g	g
8866	1" F x 3/4"M	606	4 / 32
8866P	1" F x 3/4"M	606	4 / 32